Project AGATE

Igor B. Morozov¹, Elena A. Morozova, and Scott B. Smithson

Department of Geology and Geophysics, University of Wyoming, Laramie WY, 82071-3006, <u>morozov@uwyo.edu</u> ¹Also at: Department of Geological Sciences, University of Saskatchewan, 114 Science Place, Saskatoon, SK S7N5E2 Canada, <u>igor.morozov@usask.ca</u>

Leonid N. Solodilov

Centre for Regional Geophysical and Geoecological Research (GEON), Moscow, Russia

Digitization, editing, and delivery of this data sets to IRIS is sponsored by grants from the Defense Threat Reduction Agency (DTRA01-01-C-0081; 75% of funding) and NSF (EAR-0092744; 25%).

Data summary

Project AGATE included five seismic profiles two of which recorded PNE AGATE. Locations and the approximate lengths of the profiles are (Figure 1):

Profile 1: Czech Lip – Pai-Hoi; 689 km; 3 shot points;



Profile 4: River Onega - Czech Lip; 715 km; 11 shot points; Profile 5: River Vaga – White Sea, 730 km; 7 shot points.

PNE AGATE (Sultanov et al., 1999) was recorded by two of these lines (Figure 2). Note that for the PNE, profile 1 was laid out somewhat differently

Data were acquired by Center GEON in 1985. Recording systems: Portable 3-component analogue systems TAIGA and CHEREPAKHA, 1-Hz sensors



Data format

Data format is identical to that of QUARTZ records delivered earlier. The data are provided in standard SEGY format using IBM floating point representation of data values. Geographic coordinates of shots and receivers (in degrees), and offsets (in meters) are loaded in trace headers. Recording station numbers were loaded in SEGY headers as CHANNEL, and the FFIDs correspond to shot numbers. Each data file contains a single component of recordings from one shot.

For the PNE, file names follow the following convention:

agate-1-<profile_number>-<component_index>.segy

where profile_number is the number of recording line (Figure 2). For chemical shots, the files are named as follows:

```
agate-<profile_number>-<shot_number>-<component_index>.segy
```

where profile numbers are shown in Figure 1, and shot numbers correspond to the number of the nearest receiver. The component_index is 'v' for the vertical (upward), 'r' for radial (directed away from the shot), and 't' for the transverse (directed to the right when looking away from the shot point).

Reference

Sultanov, D. D., J. R. Murphy, and Kh. D. Rubinstein (1999). A seismic source summary for Soviet Peaceful Nuclear Explosions, Bull. Seism. Soc. Am., 89, 640-647.